

Impact of Sealed Joints on Performance of Thin Whitetopping at MnROAD

Transportation Research Board 91st Annual Meeting
January 25th, 2012

Tom Burnham, P.E.
Minnesota Department of Transportation



Office of Materials and Road Research

Outline


- Whitetopping
- Joint sealing concepts
- MnROAD Test Sections
- Test Section Performance
- Conclusions and Recommendations

Whitetopping



- A pavement rehabilitation technique
- Concrete over distressed asphalt pavement
- Asphalt milled to maintain grade and improve layer bonding
- More often an “inlay” than an “overlay”
- Typically concrete layer thicknesses range = 3” to 7.5”
- Smaller panel sizes for thinner overlays


Whitetopping



Typical terms

- Ultrathin Whitetopping (UTW) = 3" to 4.5" [Requires bond]
- Thin Whitetopping (TWT) = 5" to 7.5" [Bond adds life]
- Bonded Concrete Overlays of Asphalt Pavements (BCOA) = UTW
- Unbonded Concrete Overlays of Asphalt Pavements (UBCOA) = TWT

MnROAD Cell 61



History in Minnesota


- First “modern” project
 - Olmsted County CSAH 10 (1982) [6” TWT]
- First Mn/DOT project (included test sections)
 - TH30 Amboy (1993) [6” TWT]
- Test Sections
 - MnROAD UTW & TWT (1997) [3”, 4”, 6”]
 - MnROAD TWT (2004) [4” to 5”]
 - MnROAD TWT (2008) [6”]
- First Mn/DOT “production” project
 - I-35 North Branch (2009) [6” TWT]

History in Minnesota


- Other Minnesota projects
 - Kellogg Blvd St. Paul (2000)
 - CSAH 7 Hutchinson (2009)
 - CSAH 46 Albert Lea (2009)
 - TH23 Marshall (2009/10)
 - CSAH 9 Harris (2010)
 - TH 56 West Concord (2010)
 - Olmsted County CSAH 22 (2011)
 - Anoka County CSAH 22 & CSAH 18 (2011)
 - McLeod County CSAH 2 & CSAH 25 (2011)

Many others currently under consideration as option in Alternate Bid projects

Why Seal or Fill Joints?



Unsealed joints fill with water due to “bathtub” design




Results:

- Water deteriorates bond between layers
- Panels crack due to loss of support
- Ice expansion can move panels apart = more water in joint
- Water erosion deteriorates asphalt shoulders

Why Seal or Fill Joints?



MnROAD Test Sections (2004)



- Cells 60 and 62 constructed with single saw cut joints filled with hot-pour asphalt sealant
- Cells 61 and 63 constructed with no sealant
- Panel size = 5 ft. L x 6 ft. W [1.52 m L x 1.83 m]

Traffic



- I-94 live interstate traffic
- “Accelerated” loading for 4” and 5” PCC
- CESAL’s 2004-2011 = 6.5 million

Performance



Sections with sealed/filled joints performed better!

Panel Cracking (Fall 2010)



Unsealed Joints

4" PCC = 55% cracked panels

5" PCC = 8% cracked panels



Sealed Joints


4" PCC = 11% cracked panels

5" PCC = 11% cracked panels

Distress Survey

CELL 63
50 - 100 ft

4 inch PCC with unsealed joints




Cell 63 (Fall 2010)

4 inch PCC with unsealed joints



Cracked and “shattered” panels

Cell 63 Cracked and Shattered Panels



Cell 63 (Spring 2011)

4 inch PCC with unsealed joints



Joints sealed in Fall 2010 to slow deterioration

Cell 63 (2010)

4 inch PCC with unsealed joints




Widening joints

Spalling

Distress Survey

CELL 62
100 - 150 ft

4 inch PCC with sealed joints



Cell 62 (2010)

4 inch PCC with sealed joints



“Tight” joints (virtually no spalling)



Unbonded, with some HMA deterioration


Distress Survey

CELL 61
0 - 50 ft

Cell 61


* No joints sealed

5 inch PCC with unsealed joints



Cell 61 (2010)

5 inch PCC with unsealed joints



Spalling




Unbonded, with some HMA deterioration

Distress Survey

CELL 60
100 - 150 ft

5 inch PCC with sealed joints



Cell 60 (2010)

5 inch PCC with sealed joints




“Tight” joints (virtually no spalling)



Unbonded, no HMA deterioration

Performance



Sealing Cost Beneficial?

- Narrow joints, but a lot of them!
- Cost of hot pour asphalt sealant for Cell 60
 - 220 ft long, all joints, including lane/shoulder
 - Approx. 21 gals of sealant @ \$0.60/lb= \$107.10
 - Approx. \$2600/mile
 - Labor cost? (Usually bid as incidental)

Conclusions

- MnROAD ultrathin (4") whitetopping test sections have shown a significant difference in performance related to joint sealing
 - Loss of critical layer bonding and heavy traffic have resulted in substantial cracking in panels with unsealed joints

- MnROAD thin (5") whitetopping test sections have shown a noticeable difference in joint performance related to joint sealing
 - Widening joints
 - Increased joint spalling

Recommendations

- Seal joints in whitetopping inlays
 - Protects layer bonding = slows panel cracking
 - Reduces joint spalling/panel separation
 - Extends shoulder life
- Determine cost effectiveness of sealing for thicker whitetopping designs
 - Currently monitoring 6" thick MnROAD whitetopping Cells 114-914, constructed in 2008 with unsealed joints
- Provide adequate drainage path for water
 - Keep the water out, or find a way to get it out fast!

Questions?